



F-compression connector 5.1/6.8 short, 100 pcs.
bag

Art. Number 153224



TRIAX F-compression connector 5.1/6.8 short

Technical Specifications

ORDER INFORMATION

EAN Number 5702661532245

SHIELDING

Shielding @ 1 GHz | dB > 115 dB

CHARACTERISTICS

Cable type KOKA 600, KOKA 80, KOKA 6

Tool 360920

FREQUENCY RANGE

Frequency range | MHz 0.3-3000 MHz

LOSS

Insertion loss (typ.) | dB < 0.01 @ 860-1000 MHz dB

RETURN LOSS

Return Loss | dB -36.0 @ 860-1000 MHz dB

ELECTRICAL

Impedance | Ω 75 Ω

OPERATIONAL

Temperature - operating | °C -40...100 °C

MECHANICAL



Technical Specifications

Plating	Nitin
Colour	Red
Packing QTY	100
Product Height mm	27 mm
Product Width mm	10 mm
Product Depth mm	10 mm
Packaging Height m	0.190 m
Packaging Width m	0.115 m
Packaging Depth m	0.000 m
Packaging Volume m3	0.000 m3
Net Weight kg	0.008 kg
Tara Weight kg	0.000 kg
Total Weight kg	0.008 kg