

TDH 800 Cabinet - Main Unit

Art. Number 692890



TDH 800. Technology, that can do more.

The cabinet is designed as one system of input and output signals, as such up to 24 PAL programmes or 24 QAM channels are possible; it is extremely compact and can therefore be easily installed on a wall or in a 19" rack. Whether it is related to the installation, maintenance or repair all inputs, outputs and cables can be easily installed and operated from the front of the TDH 800.

The HF output level of the integrated TDH 800 output amplifier can be software-adjusted within the range 85 dB μ V through 93 dB μ V.

Technical Specifications

ORDER INFORMATION

EAN Number 5702666928906

CHARACTERISTICS

Max. LNB control | mA 4 x 305 mA

Output level max. @ 60 dB IMD - 24 combined 93 dB μ V

FREQUENCY RANGE

Frequency range (RF OUT) | MHz 47-862 MHz

RETURN LOSS

Return loss (RF OUT) | dB > 10 dB

OPERATIONAL

Temperature - storage | °C -20 ..70 °C

Humidity - storage | % 10 to 90 %

CONNECTORS

External RF OUT F-connector

PC interface RJ 45



Technical Specifications

MECHANICAL

Packaging Height m	0.390 m
Packaging Width m	0.550 m
Packaging Depth m	0.330 m
Packaging Volume m ³	0.071 m ³
Net Weight kg	10.180 kg
Tara Weight kg	0.000 kg
Total Weight kg	10.180 kg