


TRIA
connecting the future


DIGI 10, LTE 700, Ch 21-48 (Color box)

Article number: 105460

Product description:

TRIA X UHF LTE 700 Aerials

Disruption free installation from rooftop to outlet.

- Interference protection from LTE 700 & 800 signals
- Quick and easy installation with semi-assembled aerials
- Mechanical filtering for higher gain
- Reliable high-quality aerials secures end-consumer satisfaction
- Corrosion and weather proof dipole housing
- Designed to receive DTT signals in the 470...694 MHz range
- Access to reliable, expert support from TRIAX

Specifications

ORDER INFORMATION	
EAN Number	5702661054600
CHARACTERISTICS	
Type	Digi 10
FREQUENCY	
Band (frequency)	BIV/V
Channels	21...48
Frequency range UHF	470...694 MHz
LTE protection	700
GAIN	
Gain	max 13 dBi
Gain @ 474 MHz (Ch. 21)	9.5 dBi
Gain @ 694 MHz (Ch. 48)	12.1 dBi
Gain @ 602 MHz (Ch. 37)	9.2 dBi
LOSS	
Rejection @ 758 MHz (Ch. 56)	4.3 dB
Rejection @ 788 MHz (Ch. 60)	7.6 dB
ELECTRICAL	

Front to back ratio - horisontal	15 dB
CONNECTORS	
Connector Type	F-female
MECHANICAL	
Beamwidth horisontal	±30 °
Bracketry	Mast
Elements	10
Packaging Depth	1,100 m
Packaging Height	0,075 m
Total Weight	1,130 kg
Packaging Width	0,210 m
Product Length	1085 mm
Main Material	Aluminium
Net Weight	0,730 kg
Packing QTY	10
Tara Weight	0,400 kg
Packaging Volume	0,017 m3
Product Width	480 mm
Windload	22 N