

UNIX 52, LTE 700, Ch 21-48 (Color box)

Art. Number 105560



## TRIAX UHF LTE 700 Aerials

Disruption free installation from rooftop to outlet.

- Interference protection from LTE 700 & 800 signals
- Quick and easy installation with semi-assembled aerials
- Mechanical filtering for higher gain
- Reliable high-quality aerials secures end-consumer satisfaction
- Corrosion and weather proof dipole housing
- Designed to receive DTT signals in the 470...694 MHz range
- Access to reliable, expert support from TRIAX

## Technical Specifications

### ORDER INFORMATION

EAN Number 5702661055607

### CHARACTERISTICS

#### FREQUENCY RANGE

Band UHF  
 Channels 21...48  
 Frequency range UHF | MHz 470...694 MHz  
 LTE protection @ 700Mhz

#### GAIN

Gain | dBi 14.5 max dBi  
 Gain @ 474 MHz (Ch. 21) | dBi 12.3 dBi

#### LOSS

Rejection @ 788 MHz (Ch. 60) | dB 8.1 dB

#### ELECTRICAL

Front to back ratio - horizontal | dB 20 dB



## Technical Specifications

### MECHANICAL

Beamwidth horizontal   °	±25 °
Bracketry	Mast bracket - rear
Product Depth   mm	890 mm
Elements	52
Packaging Depth   m	0.455 m
Packaging Height   m	0.085 m
Total Weight   kg	2.185 kg
Packaging Width   m	0.945 m
Product Height   mm	80 mm
Product Length   mm	1394 mm
Main material	Aluminium
Net Weight   kg	1.340 kg
Packing QTY	1
Remarks	
Tara Weight   kg	0.845 kg
Packaging Volume   m <sup>3</sup>	0.036 m <sup>3</sup>
Product Width   mm	450 mm
Windload @42 m/s   N	96 N