



EoC Ethernet WiFi Endpoint

Art. Number 383230



EoC Ethernet WiFi Endpoint

The EoC Ethernet WiFi Endpoint, with dual band concurrent Wi-Fi, is used in conjunction with the Triax Ethernet over Coax Controller (EoC) and is intended to provide Wi-Fi access in rooms without Coax cables. This is often the case for rooms such as conference rooms, corridors, lobbies, bars, etc.

The PoE Access Point is powered via Ethernet (PoE) to make the installation easy and independent of a power outlet. This will require the installation of a e PoE+ compliant Ethernet switch connected to the EoC Controller.

The PoE Access Point also has a PoE output (passthrough) to supply power to other PoE devices. This could be a 2nd PoE Access Point, an IP phone, a Camera or other devices in the same room.

If the PoE output is not used, the AP can be switched to power save mode to accept a reduced PoE input power.

Main features

- 2,4 GHZ Wi-Fi 802.11b/g/n MIMO
- 5 GHz Wi-Fi 802.11ac MU-MIMO
- 2x Ethernet port
- PoE input: PoE-in 802.3af / PoE+in 802.3at
- PoE output: PoE-out 802.3af
- VLAN support
- Layer 2 Isolation
- Powersupply requirements:
- PoE (802.3af) 15.4W when NO PoE powered device on PoE output (Ethernet 2)
- PoE+ (802.3at) 30W when PoE powered device on PoE output (Ethernet 2)

Technical Specifications

ORDER INFORMATION

EAN Number 5702663832305

triax.com



connecting the future

Technical Specifications

CHARACTERISTICS

ELECTRICAL

Ethernet interface - standard PoE-in 802.3af/at

Impedance | Ω 100 Ω

OPERATIONAL

DC Current consumption | mA 750 @13.5Vdc (PoEout: 2100mA @13.5Vdc) mA

Ethernet Interface 10/100/1000
PSU/adapter Art number 383801
Humidity - operating | % 20...80 %

 Humidity - storage | %
 10...90 %

 AC Supply voltage | VAC
 100...240 @50/60Hz VAC

PoE out max. 15.4W (802.3af)

Power Consumption (typ.) | W 10 (28W@PoEout) W PSU/adapter INFO Optional

Temperature - operating | °C -10...40 °C

Temperature - storage | °C -20 ..70 °C

CONNECTORS

Connector DC DC jack 5.5mm/2.1mm (IEC A)

Connector LAN RJ45 female
Connector OUT RJ45 female

MECHANICAL

Colour White

Dimensions product (H x D x W) | mm $37 \times 119 \times 185 \text{ mm}$

Packaging Depth | m 0.145 m
Packaging Height | m 0.060 m

Total Weight | kg 0.510 kg
Packaging Width | m 0.295 m

Net Weight | kg 0.389 kg
Packing QTY 1

Tara Weight | kg 0.121 kg
Packaging Volume | m3 0.003 m3

24-10-2023 2/2 triax.com