

M. Fibre



Satellite Reception | Terrestrial Reception | IPTV | Dishes | Amplifiers | Receivers | Headends | Antennas

M. Fibre

FIBRE

Fibre Optics Category Index

M. Fibre

m.1 Transmitters

m.2 Receivers

m.3 Taps / Splitters

m.3.1 FC/PC Products

m.3.2 SC/APC Products

m.4 Connectors / Attenuators

m.5 Fibre Cables / Patch Leeds

m.5.1 FC/PC Products

m.5.2 SC/APC Products

m.7 Enclosures

m.1 Transmitters

307372

TMDS 1230 PSU 20v 3.3Amp PSU for use with TOST + TOCT

Providing up to 3.0A of current even large cascadable systems can be powered from one PSU unit $\,$

Used for TOST 307790 and TOCT 307791

UPC 5702663073722

Brand: Triax

Brand: Triax

307790

TOST Optical Sat Transmitter

ntegrated services on a single fibre

SAT-IF distribution over fibre optics (FO) can supply many households over larger distances, with feed from a central satellite dish station.

Almost lossless transmission of satellite, DVB-T and DAB signals. Attenuation per 1000 m only about 0.3 dB.

Future-proof and widest possible variety of channels.

Space-saving installation - a 3 mm optical fibre replaces five 7 mm coaxial cables.

UPC 5702663077904

Brand: Triax

TOCT Optical Combined Transmitter

Integrated services on a single fibre

SAT-IF distribution over fibre optics (FO) can supply many households over larger distances, with feed from a central satellite dish station.

Almost lossless transmission of satellite, DVB-T and DAB signals. Attenuation per $1000\ m$ only about $0.3\ dB$.

Future-proof and widest possible variety of channels.

Space-saving installation - a 3 mm optical fibre replaces five 7 mm coaxial cables.

UPC 5702663077911

Brand: Triax

m.2 Receivers

307773

TRIAX

(DC

TWOC Wideband OPTO converter

Integrated services on a Single fibre

SAT IF distribution over fibre optics (FO) can supply many households over larger distances, with feed from a central satellite dish station.


Almost lossless transmission of satellite, DVB-T and DAB signals. Attenuation per $1000\ m$ only about $0.3\ dB$.

Future-proof and widest possible variety of channels.

Vertical and Horizontal Wideband IF signals are transmitted over one optical fibre using a Wideband LNB.

Space-saving installation - a 3 mm optical fibre replaces five 7 mm coaxial cables.

The TWOC has 2 Wideband outputs, Vertical and Horizontal.



307791





m.2 Receivers



Amplifiers 307774 TWCT Wideband OPTO converter +TER Integrated services on a Single fibre **Brand:** Triax SAT IF distribution over fibre optics (FO) can supply many households over larger distances, with feed from a central satellite dish station. TRIAX Almost lossless transmission of satellite, DVB-T and DAB signals. Attenuation per 1000 m only about 0.3 dB. Future-proof and widest possible variety of channels. TWCT Art. no.: 307774 Vertical and Horizontal Wideband IF signals are transmitted over one optical fibre Optical input | 1310 - 1330 - 1550 nm RF output | 5 - 2400 MHz using a Wideband LNB. Space-saving installation - a 3 mm optical fibre replaces five 7 mm coaxial cables. CE Product of TE The TWCT has 2 Wideband outputs, Vertical and Horizontal and a separate Terrestrial output

m.3.1 FC/PC Product

307635

Triax TOS04D 4 way optical splitter

Triax fibre optical TOS 04 - 4 way passive splitter / coupler units build passive optical networks (PON) in virtually any size and split ratio. Using combinations of the 2,3,4 & 8 Way optical splitters

All 1310/1550 nm

Complete with FC/PC Connections.

Size: 100 x 100 x 25mm

Remarks: Insertion loss 6.9dBm Triax TOS02D 2 way Optical Splitter



Triax fibre optical TOS 02 - 2 way passive splitter / coupler units build passive

optical networks (PON) in virtually any size and split ratio. Using combinations of the 2,3,4 & 8 Way optical splitters

Complete with FC/PC Connections.

Size: 150x114x20mm Remarks: Insertion loss 3.6dBm

All 1310/1550 nm

Brand: Triax

Brand: Triax

End of Line: 🚺

End of Line:

307731

Triax Fibre TOS02D- 2080 Optical Tap

Triax fibre optical TOS passive coupler units build passive optical networks (PON) in virtually any size and split ratio.

Coupler/Split Ratio: 20/80%

All 1310/1550 nm

Brand: Triax



Triax TOS02D-3070 Optical Tap

Triax fibre optical TOS passive coupler units build passive optical networks (PON) in virtually any size and split ratio.

Complete with FC/PC Connections Remarks: Through/Tap Loss 1.5/7.6dBm

Complete with FC/PC Connections. Remarks: Through/Tap Loss 2.1/5.8dBm

Coupler/Split Ratio: 30/70%

All 1310/1550 nm

Brand: Triax

End of Line:

307734

TOS 16F, 16-way FC/PC

TOS 16F, 16-way PLC Splitter FC/PC

The balanced coupler is implemented in a valid metal housing

pre-assembled with FC/PC connectors

PLC (Planar Lightwave Circuit) couplers with a wide window of wave lengths

Low and flat insertion loss

Insertion loss (typ.) Size: 175x50x155 mm 13.6 dB **Remarks:** Opti<u>cal - FC/PC 13.6 dB</u>

Brand: Triax

End of Line: V

307735

TOS 32F, 32-way FC/PC

TOS 32F, 32-way PLC Splitter FC/PC

The balanced coupler is implemented in a valid metal housing

pre-assembled with FC/PC connectors

PLC (Planar Lightwave Circuit) couplers with a wide window of wave lengths

Low and flat insertion loss

Insertion loss (typ.) Size: 175x50x155 mm 16.7 dB **Remarks:** FC/PC 16.7dB End of Line: 📝

Brand: Triax



THE REAL PROPERTY.

M. Fibre Optics

m.3.2 SC/APC Products



tellite Reception | Terrestrial Reception

Brand: Triax

Brand: Triax

Brand: Triax

Brand: Triax

m.3.2 SC/APC Products

TOS 02 SC 2 Way PLC Splitter (SC/APC)

The optical splitter uses a planar light wave circuit (PLC) based on silica optical waveguide technology. It features small size, high reliability, wide operating wavelength range and good channel-to-channel uniformity. The splitter circuit is packaged in a plastic cassette and are terminated with SC/APC

connectors. The cassette can be mounted:

- on the wall
- in 19" 3HU rack
- in TRIAX Fibre Distribution Cabinet TOS-Cab16 (307910) or TOS-Cab32 (307911)

Size: 130x113x25 mm Remarks: 3.7dBm Loss

TOS 03 SC 3 Way PLC Splitter (SC/APC)

The optical splitter uses a planar light wave circuit (PLC) based on silica optical waveguide technology. It features small size, high reliability, wide operating wavelength range and good channel-to-channel uniformity.

The splitter circuit is packaged in a plastic cassette and are terminated with SC/APC connectors. The cassette can be mounted:

- on the wall
- in 19" 3HU rack
- in TRIAX Fibre Distribution Cabinet TOS-Cab16 (307910) or TOS-Cab32 (307911)

Size: 130x113x25 mm Remarks: 5.6 dBm Loss



TOS 04 SC 4 Way PLC Splitter (SC/APC)

The optical splitter uses a planar light wave circuit (PLC) based on silica optical waveguide technology. It features small size, high reliability, wide operating wavelength range and good channel-to-channel uniformity.

The splitter circuit is packaged in a plastic cassette and are terminated with SC/APC connectors. The cassette can be mounted:

- on the wall
- in 19" 3HU rack
- in TRIAX Fibre Distribution Cabinet TOS-Cab16 (307910) or TOS-Cab32 (307911)

Size: 130x113x25 mm Remarks: 6.6 dBm Loss

307905

TOS 08 SC 8 Way PLC Splitter (SC/APC)

The optical splitter uses a planar light wave circuit (PLC) based on silica optical waveguide technology. It features small size, high reliability, wide operating wavelength range and good channel-to-channel uniformity.

The splitter circuit is packaged in a plastic cassette and are terminated with SC/APC connectors. The cassette can be mounted:

- on the wall

- in 19" 3HU rack
- Fibre Distribution Cabinet TOS-Cab16 (307910) or TOS-Cab32 (307911)

Size: 130x113x25 mm Remarks: 9.6 dBm Loss

TOS 16 SC 16 Way PLC Splitter (SC/APC)

The optical splitter uses a planar light wave circuit (PLC) based on silica optical waveguide technology. It features small size, high reliability, wide operating wavelength range and good channel-to-channel uniformity.

The splitter circuit is packaged in a plastic cassette and are terminated with SC/APC connectors. The cassette can be mounted:

- on the wall
- in 19" 3HU rack
- in Fibre Distribution Cabinet TOS-Cab16 (307910) or TOS-Cab32 (307911)

Size: 130x113x52 mm Remarks: 13.0 dBm Loss **Brand:** Triax





m.3.2 SC/APC Products



| Satellite Reception | Terrestrial Reception |

IPTV

shes | Amplifiers | Receiver

eadends | Ant

Brand: Triax

307907

703.73.50 TOS 73.75.50

DATE AND A STATE OF

TOS 32 SC 32 Way PLC Splitter (SC/APC)

The optical splitter uses a planar light wave circuit (PLC) based on silica optical waveguide technology.

It features small size, high reliability, wide operating wavelength range and good channel-to-channel uniformity.

The splitter circuit is packaged in a plastic cassette and are terminated with SC/APC connectors.

The cassette can be mounted in a 19" 3HU rack

Size: 130x113x102 mm **Remarks:** 16 dBm Loss

m.4 Connectors / Attenuators

307001

TFA 03 SC/APC - opt. att 3dB



TFA 03 - Optical attenuator
3 dB optical attenuator, SC/APC

Brand: Triax

307002

TFA 05 SC/APC - opt.att 5dB



TFA 05 - Optical attenuator 5 dB optical attenuator, SC/APC

Brand: Triax

307003

TFA 10 SC/APC - opt.att 10dB



TFA 010 - Optical attenuator. 10 dBm optical attenuator, SC/APC Brand: Triax

307684

Triax Barrel Adaptor for FC/PC-FC/PC



TFB 001 - Barrel adaptor - FC/PC - FC/PC Triax fibre optic accessories- for building optical networks Joint 2 Optical Cables.

Brand: Triax

Remarks: FC/PC

307686 Triax Barrel Adaptor for FC/PC-SC/PC



TFB 002 - Barrel adaptor - FC/PC - SC/PC
Triax fibre optic accessories- for building optical networks

Brand: Triax

307688

TFA005, 05 dBm Optical Attenuators



TFA 005 - Optical attenuator. 5 dBm optical attenuator, FC/PC-FC/PC

Brand: Triax



m.4 Connectors / Attenuators



| Satellite Reception | Terrestrial Reception | IPTV | Dishes | Amplifiers | Receivers | Headends | Antennas |

307690 TFA010, 10 dBm Optical Attenuators

TFA 010 - Optical attenuator. 10 dBm optical attenuator, FC/PC-FC/PC



307692 TFA015, 15 dBm Optical Attenuator

TFA 015 - Optical attenuator. 15 dBm optical attenuator, FC/PC-FC/PC **Brand:** Triax



FC/PC Adaptor to SC/APC - Quick Connect

Fibre Adaptor. Handy to carry in your kit. Connects from FC/PC to SC/APC.



Brand: Triax



m.5 Fibre Cables/ Patch Leads

FC/PC to FC/PC Yellow 1.5M Patch Leed

Optical patch cable - FC/PC - FC/PC - singlemode 1.5 metre

Pre-connected cables for easy installation, for singlemode use, LSZH yellow

Brand: OEM



LC-FC UPC Single Mode 1m Patch Lead

LC-FC UPC Simplex Single Mode Fibre Patch Lead 2.0mm PVC(OFNR)

Brand: OEM



m.5.1 FC/PC Range

307581 Triax FC/PC Pigtail Cable 1mtr

FC/PC Pigtail cable. Brand: Triax



Triax armored fibre optical patchcord - for building optical networks. diameter \tilde{A}^{\sim} : 3 mm. Cable length 1 meter.

Size: 1M

Optical patch cable - FC/PC - SC/APC

Optical patch cable - FC/PC - SC/APC - singlemode Brand: Triax



Pre-connected cables for easy installation, for singlemode use, LSZH grey

Size: 2M Remarks: FC/PC - SC/APC

Triax Optical Cable 1mtr

TFC 01 - Steel armored 1 metre single mode fibre optic cable - G657A, 9/125 μm. **Brand:** Triax

Pre-connected FC/PC cables for easy installation.

Low attenuation of 0.3 dB per km

UV-resistant LSZH

Steel-reinforced jacket for protection and tension

Size: 1M Remarks: Conectors FC/PC



m.5.1 FC/PC Range



ellite Reception | Terrestrial Reception **Triax Optical Cable 3mtr** TFC 03 - Steel armored 3 metre single mode fibre optic cable - G657A, 9/125 µm. **Brand:** Triax Pre-connected FC/PC cables for easy installation. Low attenuation of 0.3 dB per km **UV-resistant LSZH** Steel-reinforced jacket for protection and tension Remarks: Conectors FC/PC 307663 **Triax Optical Cable 5mtr** TFC 05 - Steel armored 5 metre single mode fibre optic cable - G657A, 9/125 μm . **Brand:** Triax Pre-connected FC/PC cables for easy installation. Low attenuation of 0.3 dB per km **UV-resistant LSZH** Steel-reinforced jacket for protection and tension Size: 5M Remarks: Conectors FC/PC **Triax Optical Cable 10M** TFC 10 - Steel armored 10 metre single mode fibre optic cable - G657A, $9/125 \mu m$. **Brand:** Triax Pre-connected FC/PC cables for easy installation. Low attenuation of 0.3 dB per km **UV-resistant LSZH** Steel-reinforced jacket for protection and tension Size: 10M Remarks: Conectors FC/PC **Triax Optical Cable 15mtr** TFC 15 - Steel armored 15 metre single mode fibre optic cable - G657A, $9/125~\mu m$. **Brand:** Triax Pre-connected FC/PC cables for easy installation. Low attenuation of 0.3 dB per km **UV-resistant LSZH** Steel-reinforced jacket for protection and tension Remarks: Conectors FC/PC Size: 15M Triax Optical Cable 20M TFC 20 - Steel armored 20 metre single mode fibre optic cable - G657A, 9/125 µm. **Brand:** Triax Pre-connected FC/PC cables for easy installation. Low attenuation of 0.3 dB per km **UV-resistant LSZH** Steel-reinforced jacket for protection and tension Size: 20M Remarks: Conectors FC/PC **Triax Optical Cable 30mtr** TFC 30 - Steel armored 30 metre single mode fibre optic cable - G657A, $9/125 \mu m$. **Brand:** Triax Pre-connected FC/PC cables for easy installation. Low attenuation of 0.3 dB per km UV-resistant LSZH Steel-reinforced jacket for protection and tension Size: 30M Remarks: Conectors FC/PC 307670 **Triax Optical Cable 75M** TFC 75 - Steel armored 75 metre single mode fibre optic cable - G657A, 9/125 μm . **Brand:** Triax Pre-connected FC/PC cables for easy installation. Low attenuation of 0.3 dB per km **UV-resistant LSZH** Steel-reinforced jacket for protection and tension Remarks: Conectors FC/PC Size: 75M 307671 **Triax Optical Cable 100mtr** TFC 100 - Steel armored 100 metre single mode fibre optic cable - G657A, 9/125 **Brand:** Triax μm. Pre-connected FC/PC cables for easy installation. Low attenuation of 0.3 dB per km **UV-resistant LSZH**

m.5.2 SC/APC Range

Remarks: Conectors FC/PC

Steel-reinforced jacket for protection and tension

Size: 100M



m.5.2 SC/APC Range



Terrestrial Reception TSC 01 Fibre patch cord 1m SC/APC 307010 Fibre Optic patch cord **Brand:** Triax The TSC xx patch cord is a single mode cable termanited with SC/APC connectror plugs at both ends. It is recomended for indoor installations in cable ducts and cabinets of fibre optic networks used for applications like: CATV distribution and DOSIS data transmission SAT-IF and DTT distribution Other fibre optic communication systems UPC 5702663070103 307011 TSC 02 Fibre patch cord 2m SC/APC Fibre Optic patch cord **Brand:** Triax The TSC xx patch cord is a single mode cable termanited with SC/APC connectror plugs at both ends. It is recomended for indoor installations in cable ducts and cabinets of fibre optic networks UPC 5702663070110 307012 TSC 05 Fibre patch cord 5m SC/APC Fibre Optic patch cord **Brand:** Triax The TSC xx patch cord is a single mode cable termanited with SC/APC connectror plugs at both ends. It is recomended for indoor installations in cable ducts and cabinets of fibre optic networks UPC 5702663070127 307013 TSC 10 Fibre patch cord 10m SC/APC Fibre Optic patch cord **Brand:** Triax The TSC xx patch cord is a single mode cable termanited with SC/APC connectror plugs at both ends. It is recomended for indoor installations in cable ducts and cabinets of fibre optic networks used for applications UPC 5702663070134 307014 TSC 20 Fibre patch cord 20m SC/APC Fibre Optic patch cord **Brand:** Triax The TSC xx patch cord is a single mode cable termanited with SC/APC connectror plugs at both ends. It is recomended for indoor installations in cable ducts and cabinets of fibre optic networks used for applications **UPC** 5702663070141 307015 TSC 30 Fibre patch cord 30m SC/APC Fibre Optic patch cord **Brand:** Triax The TSC xx patch cord is a single mode cable termanited with SC/APC connectror plugs at both ends. It is recomended for indoor installations in cable ducts and cabinets of fibre optic networks 307016 TSC 50 Fibre patch cord 50m SC/APC Fibre Optic patch cord **Brand:** Triax The TSC xx patch cord is a single mode cable termanited with SC/APC connectror plugs at both ends. It is recomended for indoor installations in cable ducts and cabinets of fibre optic networks used for applications SC/APC to SC/PC fibre cord Optical patch cable - SC/APC - SC/PC - singlemode **Brand:** Triax Pre-connected cables for easy installation, for singlemode use, LSZH yellow Size: 1M





m.5.2 SC/APC Range Terrestrial Reception Fibre Patch Leed 3 M FC/PC - SC/PC Optical patch cable - FC/PC - SC/PC - singlemode **Brand:** Triax Pre-connected cables for easy installation, for singlemode use, LSZH yellow Size: 3M 307580 SC/APC to SC/APC Optical patch cable - SC/APC - SC/APC - singlemode **Brand:** Triax Pre-connected cables for easy installation, for singlemode use, LSZH grey Size: 2M SC/APC to SC/APC 1M Yellow Fibre Patch Cable SC APC Fiber Patch Cable optical fibre Patch cord 1m 2.0mm PVC Simplex Single **Brand: OEM** Mode Remarks: SC/APC Size: 1M SC/APC to SC/APC 2M Yellow Fibre Patch Cable **SCAPC2M** SC APC Fiber Patch Cable optical fibre Patch cord 2m 2.0mm PVC Simplex Single **Brand: OEM** Mode Remarks: SC/APC Size: 2M m.7 Enclosures 252410 **Triax PTB Medium Grey** The enclosure type PTB is designed to house the last final outdoor fibre subscriber **Brand:** Triax connection. It can be mounted inground or secured to a wall or similar structure in either streetside or free-standing applications. Comes with 3 brackets mounted. Number of subscribers max. 24 End of Line: IP Rating IP 34D, Protection class IK 10 **Size:** 1004H x 230W x 80D Remarks: Limited Stock 307910 TOS-Cab 16 Cabinet -for PLC Splitters up to 16-way Distribution box for TRIAX PLC splitters TOS xxSC, splice trays, layout pigtails to **Brand:** Triax match trunk and drop fibre cables. Can be used as fibre optic terminations of optic access network or sub-distribution points in and outdoor. - Plastic enclosure, flame retardant, aging and UV resistant - Special screw and key for its door lock - Mounting on wall or on pole - Bi-layer structure of the box: bottom for splicing and upper layer for splitting and



distribution

Size: 120 x 340 x 280mm

- Special lock device for outlet of drop cables

- 2 standard slots for TOS xxSC PLC splitter cassettes--> max splitting factor: 16

Remarks: IP 65

UPC 5702663079069

M - Pg 8



m.7 Enclosures



Satellite Reception | Terrestrial Reception | IPTV | Dishes | Amplifiers | Receivers | Headends | Antennas

307911

TOS-Cab 32 Cabinet -for PLC Splitters up to 32-way

Distribution box for TRIAX PLC splitters TOS xxSC, splice trays, layout pigtails to match trunk and drop fibre cables.


Can be used as fibre optic terminations of optic access network or sub-distribution points in and outdoor.

- Plastic enclosure, flame retardant, aging and UV resistant.
- Special screw and key for its door lock
- Mounting on wall or on pole
- $\mbox{\sc Bi-layer}$ structure of the box: bottom for splicing and upper layer for splitting and distribution
- Special lock device for outlet of drop cables
- 2 standard slots for TOS xxSC PLC splitter cassettes--> max splitting factor: 32

Size: 120 x 340 x 280mm **Remarks:** IP 65



Triax 19" Fibre Splitter Rack Case



Brand: Triax

Brand: Triax

UPC 5702663079069

