



TRIAX

connecting the future

TDcH Compact Headend 16S

Art. Number 492791





TDcH Compact Headend FTA (Free to Air)

DVB-S and DVB-S2 conversion to QAM or COFDM (switchable).

Built for both wall mounting and 19" racks and equipped with 4 DVB-S/S2 inputs, 16 DVB-S2X tuners and 16 QAM or COFDM (switchable) modulators. The TDcH compact headend is optimised and engineered to meet specific TV distribution requirements in hospitality, multi-dwelling units and related sectors with an appealing, competitive cost per service ratio.

Our brand new, intuitive platform smoothly integrates easy installation, an elegant graphical user interface, central decryption, remote access, and straightforward TV service updates with LCN.

Features

- 4 x SAT IF inputs with integrated multiswitch
- 16 x DVB-S2 tuners
- 16 x QAM or COFDM full band modulators
- Electronically adjustable output level
- Suitable for adjacent channels
- Symbol rates and modulation individually adjustable- Multiplexing & IP pool
- TV-Service Multiplexing from all inputs at each output transponder to optimize available bandwidth
- TV-Service Multiplexing at the CA-modules to reduce amount of CAM's- Integrated Satellite Channel Router (SCR) multiswitch*
- Reception of up to 4 satellite positions with each 2 polarizations and 2 frequency bands
- Transport Stream Processing
- Network Information Table (NIT) for complete headend station
- LCN (Logical Channel Numbering)- SID, TSID and ONID management
- To handle conflicts during multiplexing
- To handle changes if required- PID management
- To handle PID conflicts
- PID filtering to reduce audio channels from a TV service
- Distribute TV services multiple times with different languages
- In case of service changes to secure no new TV channel tune- EPG management
- To manage the amount of EPG-data distributed in an output transponder
- To support TVs with EPG data from all TV services without the need of retuning all transponders

Service Filtering with the option for

- Remove unwanted services
- Remove services for minimize data rate-
- Real time output load measurement
- Dashboard
- System information and overview without login
- HTML user interface via self-signed HTTPS

Technical Specifications

ORDER INFORMATION

EAN Number 5702664927918

CHARACTERISTICS

Cable - symbol rate Mbit/s	3.5...7.2 Mbit/s
Demodulator Symbolrate Msym/s	1...45 Msym/s
Demodulator Type	DVB-S2X
Demodulator Viterbi Decoder	1/2; 2/3; 3/4; 5/6; 7/8; automatically / manually



Technical Specifications

DiSEqC level	1.0
DVB-S2 Modes (8PSK)	3/5, 2/3, 3/4, 5/6, 8/9, 9/10
DVB-S2 Modes (QPSK)	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
DVB-S Modes (QPSK)	1/2, 2/3, 3/4, 5/6, 7/8
Input level dB μ V	44...90 dB μ V
LNB band selection	DiSEqC 1.0 Control 13/18VDC and 22kHz
LNB current max. mA	400 mA
LNB LO/HI programmable kHz	22 kHz
Max. Output level dB μ V	QAM 95 / COFDM 93 dB μ V
MER dB	QAM>43 / COFDM>40 dB
Modulation scheme	QAM 16, 32, 64, 128, 256
Output channel	S 21 – C 69
Output level dB μ V	QAM 85...95 / COFDM 83...93 dB μ V
Output level adjustment dB	10 dB
Output Level System dB μ V	QAM 95 / COFDM 93 dB μ V
Output QAM Modes	16, 32, 64, 128, 256
Output symbol rate Mbit/s	3,5...7,2 Mbit/s
Output Type	QAM/COFDM
Satellite - demodulation	QPSK; 8PSK
Satellite transponders	16
Spurious Signals dB	> 60dB dB
Symbol rate DVB-S2 (8PSK) Mbit/s	4.5...45 Mbit/s
Symbol rate DVB-S2 (QPSK) Mbit/s	4.5...45 Mbit/s
Symbol rate DVB-S (QPSK) Mbit/s	1...45 Mbit/s
Test Point dB	-20 dB
Transport stream	chip set prepared but not supported with SW1.0
LNB V/H programmable V/mA	13/18 V/mA
Viterbi decoder	1/2; 2/3; 3/4; 5/6; 7/8; automatically / manually

FREQUENCY RANGE

Channel Raster MHz	8 MHz
Channels	S 21 – C 69
Input frequency range MHz	950...2150 MHz
Number of channels	16 channels in a row, single channel can be switched off
Output frequency range MHz	306...862 MHz
Satellite - frequency range MHz	950...2150 MHz

RETURN LOSS

Output Return Loss dB	>10 dB
Return loss SAT inputs dB	> 10 dB
Return loss (RF OUT) dB	> 10 dB

ELECTRICAL



Technical Specifications

Number of RF outputs 1

OPERATIONAL

Data rate 83 Mbit/s
DC Supply Voltage | VDC 5 VDC
Ethernet Interface 2 x 1000 Base-T (RJ 45)

CONNECTORS

Connector - SFP cage 1 x 1000 Base-T (SFP)
Connector IN F connector
Connector SAT 4 x F connector, 75 Ohm, 400 mA per input LNB power feed
Connector USB USB 2.0, Type A con (Data transfer, additional storage, ...)
External RF OUT 1 x F connector 75 Ohm
Input Type SAT-IF
Output connectors 1 x F connector 75 Ohm
Output connectors (for RF) 1 x F connector, 75 Ohm
Output connector F connector
Connector SAT-IF 4 x F connector, 75 Ohm, 400 mA per input LNB power feed
SFP cage 1 x 1000 Base-T (SFP)
USB port USB 2.0, Type A con

MECHANICAL

Clips/Grounding strap Ground clamp
Packaging Depth | m 0.255 m
Packaging Height | m 0.120 m
Total Weight | kg 4.740 kg
Packaging Width | m 0.495 m
Net Weight | kg 3.770 kg
19" Rack mount | HE,U 2 HE,U
Tara Weight | kg 0.970 kg
Packaging Volume | m3 0.015 m3