





Measuring receiver

- · for DVB-S/S2, DVB-T/ T2* (H.264/H.265), DVB-C
- · MPEG-2/MPEG-4

Rechargeable battery

• Powerful 5000mAh battery

Screenshot function

 \cdot to back up the measurement data, transport stream



The TELESTAR SATPLUS 4 meter presents itself as the optimal companion for precise signal installation and verification. It offers comprehensive coverage of various reception options, including DVB-S/S2/T/T2/C, and meets MPEG-2 and MPEG-4 requirements. Support for MPEG-2, H.264 and even H.265 (10-bit) hardware decoding ensures seamless signal playback.

TELESTAR SATPLUS 4

SATPLUS 4

TELESTAR

digital combo measuring receiver

0

4 5 6 7 8 9 MUTE 0 INFO MENI

The scan options prove to be extremely flexible and versatile: Auto, Blind, Manual or NIT - according to individual needs.

DISEQC 1.0/1.1/1.2, Unicable and 0/22 kHz audio are supported, offering a wide range of options for reception systems. Thanks to the integrated lithium-ion battery (7.4 V/5000 mAh), extensive measurements are possible, which can be displayed on the 7-inch TFT-LCD screen in a variety of presentations. These and many other useful features make the SATPLUS 4 a perfect addition for the installation of various reception paths.

practical

accessories

TELESTAR

Highlights

- · Measuring receiver for DVB-S/S2/T/T2/C and MPEG-2/MPEG-4
- · Support of MPEG-2, H.264 and H.265 (10 bit) hardware encoding
- · DISEQC 1.0/1.1/1.2, Unicable and 0/22 kHz audio are supported
- · Spectral analysis for checking the entire frequency range and constellation diagram for graphical representation of the signal quality
- · High-resolution 7-inch TFT LCD screen

- TOT - 3

» including

- · Lithium-ion battery with a capacity of 7.4 V/5000 mAh
- · Scan options such as Auto, Blind, Manual or NIT
- · Screenshot function for saving the measurement data
- · Supports WiFi and Ethernet connections

Scope of delivery

· TELESTASR SATPLUS 4, operating instructions, high-quality case, mains adapter, BNC adapter, HF adapter

Connections

- · 1x LNB-In
- · 1x Ant-In
- ·1x HDMI-In
- · 1x HDMI-Out
- · 1x AV-In
- · 1x AV-Out

- · 1x USB
 - · 1x LAN
 - · 1x fibre optic connection
 - · 1x DC In
 - · 1x DC Out



www.telestar.de

TELESTAR

TELESTAR-DIGITAL GmbH Am Weiher 14 D-56766 Ulmen/GERMANY

Phone +49 - (0) 26 76 / 9 52 00 Fax +49 - (0) 26 76 / 9 52 01 00 E-mail Verkauf@telestar.de

device (WxHxD) dimensions (cm) 26 x 18,1 x 6 weight 1,17 kg

