

Switch 24 GE + 4 x 10G SFP+ L2/L3 Managed



DESCRIPTION

The SWI024G is an L2/L3 manageable switch equipped with 24 Gigabit RJ45 ports and 4 10G SFP+ slots..

With abundant L3 management features supported, the SWI024G is capable of delivering high throughput to even the most demanding edge-of-network workgroups, while in small networks it can act as a backbone for Gigabit switches and high-speed servers. 4 SFP+ slots provide greater network flexibility.

The SWI024G is designed exclusively for the networking needs of growing business- es, with an extensive suite of management and security features available.

These devic- es are cost-effective for small and medium-sized businesses, providing ideal solutions for a variety of network scenarios.

MODELO	Switch 24 GE + 4 x 10G SFP+ L2/L3 managed
REF.	8339 SWI024G

Basic specifications

- 4x 10Gbps SFP+ Slots.
- 24 10/100/1000Mbps RJ45 ports.
- Management and administration via WEB, CLI, TELNET, SNMP
- Support IEEE 802.1Q VLAN, QoS, ACL, SSL.
- Support Spanning Tree, Multicast IPV6, SNMP.
- Support 802.1X certification.
- Support ERPS ring network.
- Support RSTP/MSTP spaning tree.
- Support Port Security, Port Monitoring and Port Isolation.
- Support Quaternary binding, ARP/IP/DoS protection.
- Mechanical Rack 19" 1U

Features

- Supports IEEE 802.3i, 802.3u, 802.3ab, 802.3z, 802.3x , 802.3az.
- Supports MAC address auto-learning and auto-aging.
- Store and forward mode operates.
- LED indicators for monitoring power, link/activity.
- Supports QoS, port mirroring, link aggregation protocol.
- 19 inches full metal iron shell and internal power adapter design, suitable for rack installation.

Energy saving and low noise

- Following the IEEE 802.3az (Energy Efficient Ethernet) standard, it greatly reduces the power consumption of the equipment and is green and energy-saving.
- Fully considering the low noise requirements of the user environment, the fanless design is adopted to monitor the temperature in the system in real time, which can effectively reduce noise pollution.

Strong business process capability:

- With IEEE 802.1Q VLAN support, the VLANs can be flexibly partitioned according to your needs.
- Supports voice VLAN, configure QoS parameters for voice data streams, enhance the transmission priority of voice data streams, and ensure call quality.
- Supports QoS, three priority modes based on Endpoint, 802.1P and DSCP, and four queue scheduling algorithms: Equ, SP, WRR and SP+WRR.
- Supports ACL, according to configure matching rules, processing actions, and temporal permissions to filter packets, and provide flexible security access control policies.
- Supports IGMP V1/V2 multicast protocol and IGMP Snooping for multi-terminal HD video surveillance and video conference access.
- Supports multicast VLAN and multicast filtering for efficient data transmission, saving network bandwidth and reducing network load.
- Supports port monitoring by copying a copy of the monitored port's packets to the monitoring port to enable network monitoring.

Complete security protection mechanism

- Supports quadruple binding of IP address, MAC address, VLAN, and port to filter packets.
- It supports ARP protection against ARP spoofing and ARP flooding attacks, such as grid spoofing and intermediary attacks, which are common in local area networks.
- Supports IP source protection to prevent illegal address spoofing including MAC spoofing, IP spoofing, and MAC/IPspoofing.
- Supports 802.1 X authentication, which provides authentication for local grid computers and controls the authorization status of the controlled endpoints based on the authentication results.
- Supports port security and stops learning when the maximum number of MAC addresses is reached to prevent MAC address attacks and control the flow of the port network.

Diverse reliability protection

- Supports STP/RSTP/MSTP spanning tree protocols, eliminating layer 2 loops and enabling link backup.
- Supports spanning tree security to prevent all forms of malicious attacks on devices in the spanning tree network.
- Static and dynamic aggregation are supported to effectively increase link bandwidth, achieve load balancing, link backup, and improve link reliability.

Operation and maintenance

- It supports a variety of management and maintenance methods such as Web-based management, CLI commands (Console, Telnet), and SNMP (V1/V2/V3).
- Supports HTTPS, SSL V3, TLSV1, SSHV1/V2 encryption for more secure management.
- RMON, system logs, and end-to-end traffic statistics for network optimization and transformation.
- Supports cable detection, Ping detection, and Tracert detection to easily analyze the faulty network nodes.
- LLDP is supported to facilitate the network management system to query and judge the communication status of the link.
- Supports CPU monitoring, memory monitoring, Ping detection, and Tracert detection.

HARDWARE SPECIFICATION

Standards	IEEE 802.3i, 802.3u, 802.3ab, 802.3x, 802.3az
Ports	24 x 10/100/1000Mbps ports, 4 x 10000Mbps SFP+ Slots, 1 x Console port
Indicators	Electrical port indicator, optical port indicator, power input indicator, system running indicator
Network Media (Cable)	10Base-T; UTP category 3, 4, 5 cable (maximun 100m) 100Base-Tx; UTP category 5, 5e cable (maximun 100m) 1000Base-Tx; UTP category 5e, 6 cable (maximun 100m) 1000Base-XMMf, SMF
Transfer Method	Store and Forward
MAC Address Table	16k
Switchng Capacity	128GBps
Packet Forwarding Rate	95,232Mpps
Packet Buffer	12Mbit
Jumbo Frame	10KBytes

CARACTERÍSTICAS DEL SOFTWARE

L3 Switching Features	<ul style="list-style-type: none"> • Static Routing - IPv4/IPv6
	<ul style="list-style-type: none"> • Address Resolution Protocol (ARP) - Dynamic ARP
L2 Switching Features	<ul style="list-style-type: none"> • 8K MAC Address Table
	<ul style="list-style-type: none"> • 10K (10000) Jumbo Frame
	<ul style="list-style-type: none"> • Flow Control - 802.3x (Full-duplex)
	<ul style="list-style-type: none"> • Spanning Tree - IEEE 802.1D (STP) - IEEE 802.1w (RSTP) - IEEE 802.1s (MSTP)/16 instances - Auto Edge Port - BPDU Filtering - ERPS
	<ul style="list-style-type: none"> • Link Aggregation - IEEE 802.3ad LACP - Static Trunk - Max 8 Group - Max 8 Ports/Group - Traffic Load Balancing

VLAN	<ul style="list-style-type: none"> • Surveillance VLAN - 16 OUI Mode (Auto/Manual)
	<ul style="list-style-type: none"> • Voice VLAN - 16 OUI Mode (Auto/Manual)
	<ul style="list-style-type: none"> • QinQ (IEEE 802.1ad) - Basic
	<ul style="list-style-type: none"> • GARP VLAN Registration Protocol (GVRP)
	<ul style="list-style-type: none"> • 4094 Static VLAN/Port-based
	<ul style="list-style-type: none"> • IEEE 802.1Q Tagged-based
	<ul style="list-style-type: none"> • 8 groups Protocol-based
	<ul style="list-style-type: none"> • 256 MAC-based
Multicast	<ul style="list-style-type: none"> • Common - 256 Multicast Groups - Immediate Leave - Static/Forbidden Router Port - Static/Forbidden Forward Port - 128 profiles Filtering - Throttling
	<ul style="list-style-type: none"> • IGMP Snooping - IGMP v1/v2 - IGMP v3 Basic (BISS) - IGMP v2/v3 Querier
	<ul style="list-style-type: none"> • MLD Snooping - MLD v1/v2
	<ul style="list-style-type: none"> • Multicast VLAN Registration (MVR) - IPv4
Quality of Service (QoS)	<ul style="list-style-type: none"> • Trusted QoS/Priority 8 Queue
	<ul style="list-style-type: none"> • Queue Scheduling - WRR - WFQ - Strict Priority - Hybrid(WRR+SP or WFQ+SP)
	<ul style="list-style-type: none"> • Class of Service - Port-based - 802.1p - IP TOS Precedence - IP DSCP
	<ul style="list-style-type: none"> • Rate Limit - Port-based (Ingress/Egress)
Access control list (ACL)	<ul style="list-style-type: none"> • ACL Type - L2/L3/L4 - 512 MAC-based - 512 IPv4-based - 512 IPv6-based
	<ul style="list-style-type: none"> • Access Rules - 1024

Security

- AAA Authentication
- 8 TACACS+
- 8 RADIUS
- Authentication Manager
 - IEEE 802.1X
 - MAC Auth
 - Web Auth
 - Guest VLAN
 - Port-based
 - Host-based
- Account Manager
 - Local Authenticoitin
 - 8 Multiple User Account
 - Multi-Level Securiy (Manager/Operator)
 - Password Recovery Procedures
- Management Access
 - Management VLAN
 - 256Management ACL
- SSL
 - SSLv2
 - SSLv3
 - TLSv1
- WebUI
 - HTTPS
- CLI
 - SSH v1/v2
- Port Security
 - 256 Dynamic Lock
- Storm Control
 - Broadcast
 - Unknown Multicast
 - Unknown Unicast
- Spanning Tree
 - BPDU Guard
- Protected Port (Port Isolation)
- Black Hole MAC
- CPU Defence Engine
- DoS Prevention
- DHCP Snooping (with Option 82)
- Dynamic ARP Inspection
- 256 IP Source Guard
- IP/MAC/Port Binding (IMPB)
- Dynamic VLAN Assignment

IPv6	<ul style="list-style-type: none"> • IPv6 Host - Auto Configuration - Static IPv6 Address and Prefix Length - Static IPv6 Default Gateway - IPv6 Neighbor Discovery (ND) - IPv6 Duplicate Address Detection - ICMPv6
	<ul style="list-style-type: none"> • IPv6 Application - HTTP/HTTPS - TELNET - SSH - SNMP - TFTP - Syslog - PING - DHCPv6

Management	<ul style="list-style-type: none"> • CLI - 3 sessions Console - 3 sessions Telnet (RFC854)
	<ul style="list-style-type: none"> • WebUI - HTTPS
	<ul style="list-style-type: none"> • SNMP(v1,v2c,v3)
	<ul style="list-style-type: none"> • File Management - Firmware Upgrade/Backup - Dual Images - Configuration Download/Backup - Multiple Configurations
	<ul style="list-style-type: none"> • Upload/Download - TFTP (RFC783) - HTTP - UART
	<ul style="list-style-type: none"> • Time Management - Local - SNTP
	<ul style="list-style-type: none"> • Port Management - Friendly Port Name (Port Description) - Error Disabled Recovery
	<ul style="list-style-type: none"> • Line Management - Console - Telnet (RFC854) - SSH v1/v2
	<ul style="list-style-type: none"> • DHCP - Client
	<ul style="list-style-type: none"> • DNS - Client
	<ul style="list-style-type: none"> • Software Reset Button
	<ul style="list-style-type: none"> • IEEE (802.3az)
	<ul style="list-style-type: none"> • 32 entries / type RMON Management

Discovery	• IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
	• ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)
Diagnostics	• UDLD
	• Mirroring - 4 sessions port-based (Many to One)
	• Syslog (RFC3164) - Local RAM - Local Flash - 8 Remote Server
	• System Diagnostics - CPU Utilization - Memory Utilization - Port Utilization - Technical Support Log
	• Port Diagnostics - Cable Test - Fiber Module Status
	• Network Diagnostics - Ping Test - Traceroute
MIB	• RFC1213 MIBII (System & Interface groups)
	• RFC2819 RMON I (1,2,3, & 9 groups)
	• RFC1215 Generic Traps
	• RFC1493 Bridge
	• RFC2674 Bridge MIB Extensions
	• RFC2737 Entity
	• RFC3635 Ethernet-Like
	• RFC2863 Interface Group
	• SNMP-Community-MIB
	• SNMPv3-MIB
Power Supply	AC100~240V 50/60Hz
Dimensions	440*190*44.5 mm
Enviroment	Operating Temperature: 0 °C ~45 °C (0T~113T) Storage Temperature: -40 °C ~70 °C (-40T ~158T) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95% non-condensing